NØRDIS

Indoor unit model name	NDI-G12TC1B
Outdoor unit model name	NDO-G12TC1

Sound power level (inside)	56	dB(A)
Sound power level (outside)	64	dB(A)

Refrigerante R32		GWP	675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO_2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling mode

SEER	9.4	
Energy efficiency class	A***	
Design load (Pdesignc)	3.5	kW
Energy consumption,	131	kWh per year,based on standard test results.

Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode (Average)

SCOP	5.1		
Energy efficiency class	A***		
Design load (Pdesignh)	2.6	kW	(-10℃)
Declared capacity	2.5	kW	(-10℃)
Back up heating capacity	0.1	kW	(-10℃)
Energy consumption,	742	kWh per year.based on standard test results.	

Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode (Warmer) Optional

SCOP	5.8		
Energy efficiency class	A***		
Design load (Pdesignh)	3.7	kW	(2℃)
Declared capacity	3.7	kW	(2℃)
Back up heating capacity	0	kW	(2℃)
Energy consumption,	894	kWh per year.based on standard test results.	

Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode (Colder) Optional

SCOP	4.0		
Energy efficiency class	A*		
Design load (Pdesignh)	3.8	kW	(-22℃)
Declared capacity	2.7	kW	(-22℃)
Back up heating capacity	1.1	kW	(-22℃)
Energy consumption,	1995	kWh per year.based on standard test results.	

Actual energy consumption will depend on how the appliance is used and where it is located.